Blue Ridge Commercial Carpet P.O. Box 507, Ellijay, GA 30540
800 354 8951, 706 276 2005, www.blueridgecarpet.com

SPECIFICATIONS

QUALITY: **C750T COLOR STRIPES** 24" X 24" Carpet Tile

COLORS: (7) 3307 Stone, 3308 Lake Bed, 3309 Canyon, 3311 Forest Floor, 3312 Prairie, 3313 Firestone, 3314 Marine Life

CONSTRUCTION	-	Pattern Loop
YARN	-	51% Eco R3 Repurposed Waste Nylon, 49% Envirolon XP Nylon with Blue Shield© Stain and Soil Protector
DYE METHOD	-	100% Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
TUFTED YARN WEIGHT	-	16 Ounces Per Sq. Yd. (543 g/m²)
FINISHED PILE THICKNESS	-	Approx. .087 Inch (2.21mm)
DENSITY FACTOR	-	6621
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	Brick or ¼ Turn
Wear Warranty	-	10 Year
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	10 Year
Colorfastness to Atmospheric Contaminants	-	5 Year
Recycling Program	-	Qualifies for the Blueridge BlueCycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:
Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. CleanStep® Walk Off Tiles by Blueridge or walk off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerance in yarn fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Carpet must be installed according to manufacturer's carpet installation procedures.